



25 MM M910 (TPDS-T) TARGET PRACTICE DISCARDING SABOT-TRACER AMMUNITION



CHARACTERISTICS

Length of complete round	223 mm (Max)
Projectile weight	97.4 g
Muzzle velocity	1535 m/s
Propellant type	Ball propellant

25 MM M910 (TPDS-T) TARGET PRACTICE DISCARDING SABOT-TRACER AMMUNITION

IN THE BATTLE SINCE 1888

Australian Munitions' 25 mm M910 TPDS-T ammunition conforms to the design parameters of NATO STANAG 4173 and is ballistically matched to the M919 APFSDS-T and M791 APDS-T cartridges. The cartridge consists of an inert projectile crimped into a steel cartridge case. The projectile consists of a steel, spin-stabilised sub-calibre core containing a consolidated tracer, a nylon discarding sabot with integral driving band and protective nose cap, and an aluminium alloy pusher plug.

The projectile is blue in colour and is inert except for the tracer. The projectile is used in training and gun system testing for the M242 25 mm automatic cannon.

Australian Munitions' 25 mm M910 TPDS-T ammunition is assembled at our Benalla munitions facility.

PACKAGING

Australian Munitions' 25 mm M910 TPDS-T ammunition can be supplied in the following standard packaging configuration:

- Linked ball: two linked belts of 15 rounds per PA125 container.

Our 25 mm M910 TPDS-T ammunition will be shipped in standard military packages conforming to the UN recommendations for transport of dangerous goods. The packages are classified as Hazard Division 1.2C, UN Number 0328, Proper Shipping Name – Cartridges for Weapons, Inert Projectile.

Details of the above mentioned packaging configurations can be supplied upon request.



10/2016
LAV image © Australian Department of Defence



The Thales Australia Centre, WTC Northbank Wharf, Concourse Level,
Siddley Street, Melbourne, Victoria 3005, Australia.

E-mail: info@australian-munitions.com.au

Web: www.australian-munitions.com.au

Thales Australia Limited trading as Australian Munitions ABN 66 008 642 751

Australian Munitions - A Thales Australia business